

PLATE DEVELOPERS AND REPLENISHERS

PD-30

Direct use developer for thermal positive plates.

PROPERTIES

- Minimum aggression of the coating in the image areas obtaining the maximum cleaning of the non images areas.
- Auto-replenisher. The multipurpose property of PD-30 permits its use as both developer and replenisher, maintaining in the bath the correct conductivity values.
- High emulsion dissolving properties to minimize the accumulation of residuals in the automatic processor.
- Long life in processor.

APPLICATION

- Development in processors for thermal plates.
- Direct use.

METHOD OF USE

- | | |
|------------------------------------|---------------------------------------|
| • Recommended working temperature: | 23 °C ± 1 °C. |
| • Development time: | 30 ± 5 seconds in immersion. |
| • Replenishment: | Use developer PD-30 as a replenisher. |
| • Replenishment rate: | 120 ml/m ² . |
| • Antioxidant Stand by ON: | 100 ml/h. |
| • Antioxidant Stand by OFF: | 100 ml/h. |

PACKAGING

- 20, 200 y 1.000 litres.

CONSIDERATIONS

- Adequate replenishment keeps filters and circulation systems clean prolonging the life of the bath.
- Correct cleaning of the equipment will avoid contamination of the new bath and prolong the life of the processor. Clean using PC-520 and PC-600.

Note: The results obtained may vary depending if the conditions of use are outside of our recommended values.